

FISH & RICHARDSON P.C.

225 Franklin Street
Boston, Massachusetts
02110-2804

Telephone
617 542-5070

Facsimile
617 542-8906

Web Site
www.fr.com

jc551 U.S. PTO
09/248371
02/08/99

February 8, 1999

Attorney Docket No.: 10525/003001

Box Patent Application

Assistant Commissioner for Patents
Washington, DC 20231

Presented for filing is a new original patent application of:

Applicant: ANTHONY M. LOVELL, SYLVAN CLEBSCH
AND GREG COCKROFT
Title: EFFICIENT TRANSMISSION OF DATA TO MULTIPLE
NETWORK NODES

Enclosed are the following papers, including those required to receive a filing date
under 37 CFR §1.53(b):

	<u>Pages</u>
Specification	9
Claims	14
Abstract	1
Signed Declaration	[To Be Filed At A Later Date]
Drawing(s)	6

Enclosures:

- Postcard.

This application is entitled to small entity status. A small entity statement will be
filed at a later date.

"EXPRESS MAIL" Mailing Label Number EL18258090805

Date of Deposit February 8, 1999
I hereby certify under 37 CFR 1.10 that this correspondence is being
deposited with the United States Postal Service as "Express Mail
Post Office To Addressee" with sufficient postage on the date
indicated above and is addressed to the Assistant Commissioner for
Patents, Washington, D.C. 20231.

Lisa G Gray
Lisa G Gray

02/08/99
jc618 U.S. PTO
Richardson
1859-1951

BOSTON
NEW YORK
SILICON VALLEY
SOUTHERN CALIFORNIA
TWIN CITIES
WASHINGTON, DC

FISH & RICHARDSON P.C.

February 8, 1999

Page 2

Basic filing fee	380.00
Total claims in excess of 20 times \$9.00	423.00
Independent claims in excess of 3 times \$39.00	117.00
Fee for multiple dependent claims	0.00
Total filing fee:	\$ 920.00

A check for the filing fee is enclosed. Please apply any other required fees or any credits to deposit account 06-1050, referencing the attorney docket number shown above.


If this application is found to be incomplete, or if a telephone conference would otherwise be helpful, please call the undersigned at 617/542-5070.

Kindly acknowledge receipt of this application by returning the enclosed postcard.

Please send all correspondence to:

Eric L. Pahl
Fish & Richardson P.C.
225 Franklin Street
Boston, MA 02110-2804

Respectfully submitted,



Lawrence K. Kolodney
Reg. No. P43,807
Enclosures

APPLICATION
FOR
UNITED STATES LETTERS PATENT

TITLE: EFFICIENT TRANSMISSION OF DATA TO MULTIPLE
NETWORK NODES

APPLICANT: ANTHONY M. LOVELL, SYLVAN CLEBSCH AND GREG
COCKROFT

"EXPRESS MAIL" Mailing Label Number EL182580908 US

Date of Deposit February 8, 1999
I hereby certify under 37 CFR 1.10 that this correspondence is being
deposited with the United States Postal Service as "Express Mail
Post Office To Addressee" with sufficient postage on the date
indicated above and is addressed to the Assistant Commissioner for
Patents, Washington, D.C. 20231.

Lisa G Gray
Lisa G Gray

EFFICIENT TRANSMISSION OF DATA TO MULTIPLE NETWORK NODES

5 Background of the Invention

 The growth of the Internet has spurred the development of many new programs and services that permit two-way communication between more than two users at the same time. Such communication may be in the form of typed
10 messages, for example in the internet relay chat (IRC) service, or as voice or video transmitted over the network.

 Typically such programs and services use the concept of a "channel" to refer to a set of network nodes that are in mutual communication with each other. When a node
15 subscribes to a channel, it receives copies of all of the messages that are transmitted over the channel. Programs and services using channels must therefore provide a mechanism for distributing packets issuing from one node on the channel to all of the other nodes on the channel.

 Two general models have been heretofore applied in this regard. In a peer-to-peer model each node is responsible for sending a copy of each packet to all of the other nodes on the channel. This model is limited, however, by the bandwidth of the node's network connection. For
20 example, if the node was connected to a network by a slow dial-up connection and the node were to transmit to more than a few other nodes on the network, this could produce excessive delays. Delays are especially significant for real time audio or video communication, since they can
25 reduce the quality of the audio or video signal received by other nodes.
30

 An alternative to the peer-to-peer model is the client-server model. In the client server model, data communicated between the various nodes subscribing to a
35 channel (referred to as "clients") are always directed

through a dedicated intermediary computer known as the
"server." In the simplest case, the server acts as a
reflector of the data packets received from clients. Each
packet received at the server is copied, with a copy
5 transmitted to every other client on the channel.

Alternatively, servers may combine data received
from multiple nodes (e.g. by mixing simultaneously received
audio signals), and transmit the combined data to the
clients on the channel.

10 Because the server is dedicated to retransmission of
data from a large number of clients, its bandwidth may be
underutilized if it is not operating at full capacity.

Summary of the Invention

The present invention provides an improved method,
15 system, and computer program product for providing
communication among multiple nodes on a network.

In one aspect, the invention is a method for
transmitting a data block over a network from a first
sending node to a first set of recipient nodes, including,
20 in the first sending node, a) dividing the first set of
recipient nodes into a subset of selected nodes, selected
according to scoring criteria associated with each recipient
node, and a subset of unselected nodes, b) assigning at
least one of the unselected nodes to at least one selected
25 node according to scoring criteria associated with the
respective selected nodes, and c) transmitting to each
selected node a packet including the data block and a list
of the nodes assigned to the selected node.

In another aspect, the invention is a method for
30 transmitting a data block over a network from a first
sending node to a first set of recipient nodes, including,
the steps of, in a selected node, a) receiving from the
first sending node the packet including the data block and a

list of assigned nodes, b) dividing the list of assigned nodes into a subset of selected assigned nodes, selected according to scoring criteria associated with each assigned node, and a subset of unselected assigned nodes, c) re-
5 assigning at least one of the unselected assigned nodes to at least one selected assigned node according to the scoring criteria associated with respective selected assigned nodes, and d) transmitting to each selected assigned node a packet including the data block and a list of the nodes re-assigned
10 to the selected assigned node.

It is therefore an advantage of the invention to provide a method and system for enabling a node in a data network, having a low effective bandwidth, to transmit data to a large number of other nodes in the network, without
15 excessive delay. It is a further advantage of the invention to provide a method and system for enabling a node in a data network to transmit data to a large number of other nodes in the network, without the use of a dedicated server.

These, and other advantages of the present
20 invention, are fully described in the following detailed description of a preferred embodiment, and in the claims.

Brief Description of the Drawings

Figure 1 shows a network for performing an embodiment of the invention.

25 Figure 2 is a schematic diagram of a packet for transmitting data on a network.

Figure 3 is a schematic diagram showing channel lists in a node.

30 Figure 4 is a flowchart showing steps taken by an embodiment of the invention.

Figure 5 is a schematic diagram of a packet used by an embodiment of the invention.

Figure 6 is a flowchart showing steps taken by an embodiment of the invention.

Description of the Preferred Embodiments

Figure 1 shows a computer network 100, such as the Internet, or a local area network, in which multiple nodes 110a-110h are connected to the network using a set of heterogeneous communication interfaces 120a-120h. Examples of such communication interfaces include 28.8 kilobaud modems, ISDN lines, T1 lines and T3 lines. Each communication interface 120a-120h has a characteristic bandwidth, measured in bits per second. A node may include any programmed electronic device capable of communicating data over a network, such as a computer workstation, a cable television interface, a personal communications system (PCS) device, and the like.

Nodes communicate by transmitting packets 200 via the network. As shown in Figure 2, each packet includes a header 210, that contains addressing information, such as an internet protocol (IP) address, and a payload 220 that contains the data to be communicated to the recipient.

Referring to Figure 3, each node on the network may, at a given time, be subscribed to one or more channels. Each node 110 maintains a channel list for each channel to which it is subscribed. A channel list 300 includes a channel ID 310, which uniquely identifies the channel, along with a set of node IDs 320, which identify every other node subscribed to the channel. Associated with each node address in the channel list 300 is an effective bandwidth value 330, a number representing the effective bandwidth of the communications interface for that node.

Channel subscription (i.e. the adding or subtracting of nodes from a channel) may be handled using any conventional method. For example, a dedicated subscription

server may be used to subscribe and unsubscribe nodes on a channel. A new node could be added to the channel by transmitting a request to the server. The server, in turn, would inform all existing channel subscribers of the
5 identity of the new member, which would update their respective channel lists 300 accordingly. Alternatively, one of the channel members could be selected to serve as the subscription server through a negotiation process between channel members.

10 When a node subscribes to a channel, it provides the subscription server with information about itself, including its effective bandwidth, which is retransmitted to the other channel subscribers to permit each subscribing node 110 to maintain an up-to-date channel list 300.

15 In general, the effective bandwidth of a node is the nominal bandwidth of the node's communications interface. However, under some circumstances, a node may provide an effective bandwidth value that is less than the nominal bandwidth of its communications interface when it cannot
20 allocate all of its bandwidth for communication on a given channel. For example, the node might already be subscribed to other communication channels, or the node may be engaged in non-channel communication.

The transmission of a data packet from a sending
25 node to other nodes in a channel will now be described. First, the sending node 110 determines the value of MAXCHAN, the maximum number of simultaneous transmission streams that it can support (step 500). MAXCHAN may be a function of the node's effective bandwidth, or may be empirically
30 determined.

Next, the sending node 110 examines the channel list 300 to determine whether there are more than MAXCHAN nodes on the channel (other than the sending node) (step 510). If

there are not more than MAXCHAN other nodes on the channel list 300, the sending node sends packets containing the data block directly to each of the nodes on the channel list (step 520). In a preferred embodiment, the packets are sent approximately simultaneously.

If there are more than MAXCHAN other nodes on the channel list, the sending node selects the MAXCHAN number of nodes on the channel list having the highest effective bandwidths (step 530).

Next, the sending node computes, for each of the selected nodes, a fair share value (step 540). This value is computed by taking the ratio of the effective bandwidth 330 for a given selected node to the sum of the effective bandwidths 330 for all of the selected nodes.

Next, the sending node assigns each of the remaining (unselected) nodes to one of the selected nodes, in approximate proportion to the fair share values computed for each selected node (step 550). In an alternative embodiment, the sending node could assign only a portion of the unselected nodes, according to a prioritization scheme, if the node determines that the number of unselected nodes exceeds an operational limit.

Next, the sending node sends a packet to each of the selected nodes (step 560). In a preferred embodiment, the packets are sent approximately simultaneously. Referring to Figure 5, the header 210 of each packet is addressed to one of the selected nodes, while the payload portion 220 of each packet includes node ID of the sending node (identified as the originator of the data block) 225 the data block 230, and a list 240 of the nodes assigned to the node to which the packet is addressed.

Referring now to Figure 6, when a packet from a sending node arrives at one of the selected nodes, it is

received (step 600), and the originator node ID 225 and data block 230 are extracted (step 610). This information can then be used at the receiving node by other processes. For example, if the data block 230 includes audio data, the data block 230 could be used to generate audio outputs at the selected node.

The receiving node then determines its MAXCHAN value, (step 620), and compares it to the number of nodes on the list of assigned nodes in the packet received from the sending node (step 630). If the number of nodes in the list is not greater than MAXCHAN, the receiving node transmits packets containing the data block 230 to each of the assigned nodes (step 640).

If the list of assigned nodes is longer than MAXCHAN, the following steps are performed. The receiving node selects the MAXCHAN nodes from the assigned nodes list having the greatest bandwidth (step 650), and then calculates a fair share value for each of the selected nodes (step 660). It then re-assigns each of the unselected assigned nodes from the list to one of the selected nodes from the list, in approximate proportion to the fair share values of each selected node (step 670). (In an alternative embodiment, the receiving node could re-assign only a portion of the unselected assigned nodes, according to a prioritization scheme, if the receiving node determines that the number of unselected assigned nodes exceeds an operational limit.) The receiving node then transmits a packet to each of the selected nodes, containing the originator node ID 225, the data block 230, plus a list of the nodes re-assigned to the node to which the packet is addressed (step 680). Each of the nodes receiving these packets processes them in a similar fashion, by executing the steps beginning at step 600. This process continues

until the data block has been distributed to all of the nodes in the channel.

In this way, the invention advantageously provides a method for distributing packets to a large number of recipient nodes on a channel, without effective limitation from the effective bandwidth of the sending node, and without using a dedicated server.

In alternative embodiments, criteria other than, or in addition to, effective bandwidth, may be used by a sending node to select recipient nodes.

In one alternative embodiment, the channel list 300 of a given node includes information identifying the latency (average delay between transmission and reception of a packet) associated with transmissions from the given node to each other node in the channel. These values are computed by the given node and updated periodically by sending test messages to the other nodes on the channel and calculating the time to receive a response. In this embodiment, nodes are selected by assigning to each a score, based on a weighted difference of the effective bandwidth and the latency of the node, and then selecting the nodes with the highest scores. Similarly, unselected nodes are assigned to selected nodes in approximate proportion to their scores, rather than their effective bandwidths.

In another embodiment, node scores are computed as a function of the effective bandwidth, latency, and recency. Recency refers to the amount of time since a data block was received that was initially sent (i.e. not merely re-transmitted as described above) by a given node. Such a function could give greater scores to nodes with lower recency values, thus making it more likely that nodes from which packets were recently received will be among the first to receive outgoing data.

In another alternative embodiment, a given unselected node may be assigned to more than one of the selected nodes, thus providing a redundant route between the sending node and the ultimate recipient for transmission of a given data block. If this resulted in multiple copies of the data block arriving at the ultimate recipient node, the ultimate recipient node would simply ignore the subsequent copies. This could be done, for example, by assigning each data block a serial number in the sending node, and comparing the serial number of each data block received by the ultimate recipient node to a list of serial numbers already received from the sending node. This embodiment would be useful where the reliability of different transmission paths in the network varies or is unknown.

The invention described herein may be implemented in software or in hardware. In particular, the invention may be implemented by programming a computer in each node to perform the steps necessary to carry out the method described herein. Programming codes for carrying such steps may be placed on a computer readable medium for convenient transport and storage.

What is claimed is:

1 1. A method for transmitting a data block over a
2 network from a first sending node to a first set of
3 recipient nodes, comprising:
4 in the first sending node:
5 dividing the first set of recipient nodes into
6 a subset of selected nodes, selected according to
7 scoring criteria associated with each recipient
8 node, and a subset of unselected nodes;
9 assigning at least one of the unselected nodes
10 to at least one selected node according to scoring
11 criteria associated with the respective selected
12 nodes;
13 transmitting to each selected node a
14 packet including the data block and a first
15 list of the nodes assigned to the selected
16 node.

1 2. The method of claim 1, wherein each unselected
2 node is assigned to at least one selected node.

1 3. The method of claim 1, further comprising:
2 in at least one recipient node:

3 receiving from the first sending node the
4 packet including the data block and the first list
5 of assigned nodes;
6 dividing the first list of assigned nodes into
7 a subset of selected assigned nodes, selected
8 according to scoring criteria associated with each
9 assigned node, and a subset of unselected assigned
10 nodes;

11 re-assigning each of the unselected assigned
12 nodes to at least one selected assigned node

13 according to the scoring criteria associated with
14 the respective selected assigned nodes;
15 transmitting to each selected assigned
16 node a packet including the data block and a
17 list of the nodes re-assigned to the selected
18 assigned node.

1 4. The method of claim 3, wherein the at least one
2 recipient node includes at least two recipient nodes.

1 5. The method of claim 3, further comprising, in
2 the first selected node, generating a user discernable
3 output reflecting information in the data block.

1 6. The method of claim 1, wherein the scoring
2 criteria for at least one recipient node includes the
3 effective bandwidth of that node.

1 7. The method of claim 1, wherein the scoring
2 criteria for at least one recipient node includes the
3 latency between the first sending node and that recipient
4 node.

1 8. The method of claim 1, wherein the scoring
2 criteria for at least one recipient node includes the amount
3 of time since a packet from that recipient node was received
4 by the first sending node.

1 9. The method of claim 1, wherein the data block
2 contains audio data.

1 10. The method of claim 1, wherein the data block
2 contains video data.

1 11. The method of claim 2, wherein each unselected
2 node is assigned to only one selected node.

1 12. The method of claim 1, further comprising:
2 in a second sending node, which is also in the first
3 set of recipient nodes:

4 dividing a second set of recipient nodes into a
5 subset of selected nodes, selected according to
6 scoring criteria associated with each recipient
7 node, and a subset of unselected nodes;

8 assigning each of the unselected nodes from the
9 second set of recipient nodes to at least one
10 selected node from the second set of recipient nodes
11 according to scoring criteria associated with the
12 respective selected nodes;

13 transmitting to each selected node from
14 the second set of recipient nodes a packet
15 including the data block and a second list of
16 the nodes assigned to the selected node.

1 13. The method of claim 12, further comprising:
2 in a second selected node:

3 receiving from the second sending node the
4 packet including the data block and the second list
5 of assigned nodes;

6 dividing the second list of assigned nodes into
7 a subset of selected assigned nodes, selected
8 according to scoring criteria associated with each
9 assigned node, and a subset of unselected assigned
10 nodes;

11 re-assigning each of the unselected assigned
12 nodes from the second list of assigned nodes to at
13 least one selected assigned node from the second

14 list of assigned nodes according to the scoring
15 criteria associated with the respective selected
16 assigned nodes;
17 transmitting to each selected assigned
18 node from the second list of assigned nodes a
19 packet including the data block and a list of
20 the nodes re-assigned to that node.

1 14. A method for transmitting a data block over a
2 network from a first sending node to a first set of
3 recipient nodes, comprising:

4 in at least one selected node in the first set of
5 recipient nodes:

6 receiving from the sending node the packet
7 including the data block and a list of assigned
8 nodes;

9 dividing the list of assigned nodes into a
10 subset of selected assigned nodes, selected
11 according to scoring criteria associated with each
12 assigned node, and a subset of unselected assigned
13 nodes;

14 re-assigning at least one of the unselected
15 assigned nodes to at least one selected assigned
16 node according to the scoring criteria associated
17 with the respective selected assigned nodes;

18 transmitting to each selected assigned
19 node a packet including the data block and a
20 list of the nodes re-assigned to the selected
21 assigned node.

1 15. The method of claim 14, wherein each unselected
2 assigned node is re-assigned to at least one selected
3 assigned node.

1 16. The method of claim 14, wherein the at least
2 one selected node includes at least two selected nodes.

1 17. The method of claim 14, further comprising, in
2 at least two of the first set of recipient nodes, generating
3 a user discernable output reflecting information in the data
4 block.

1 18. The method of claim 14, wherein the scoring
2 criteria for at least one of the nodes on the list of
3 assigned nodes includes the effective bandwidth of that
4 node.

1 19. The method of claim 14, wherein the scoring
2 criteria for at least one of the nodes on the list of
3 assigned nodes includes the latency between the assigned
4 node and the selected node.

1 20. The method of claim 14, wherein the scoring
2 criteria for at least one of the nodes on the list of
3 assigned nodes includes the amount of time since a packet
4 from the assigned node was received by the selected node.

1 21. The method of claim 14, wherein the data block
2 contains audio data.

1 22. The method of claim 14, wherein the data block
2 contains video data.

1 23. The method of claim 15, wherein each unselected
2 assigned node is re-assigned to only one selected assigned
3 node.

1 24. A computer program product residing on a
2 computer readable medium comprising instructions for causing
3 a particular network node, connected to a network having a
4 plurality of network nodes, to:

5 create a first set of recipient nodes from among the
6 plurality of network nodes;

7 divide the first set of recipient nodes into a
8 subset of selected nodes, selected according to scoring
9 criteria associated with each recipient node, and a subset
10 of unselected nodes;

11 assign at least one of the unselected nodes to at
12 least one selected node according to scoring criteria
13 associated with the respective selected nodes;

14 transmit to each selected node a packet including a
15 data block and a list of the nodes assigned to the selected
16 node.

1 25. The product of claim 24, further comprising
2 instructions for causing the particular network node to
3 assign each of the unselected nodes to at least one selected
4 node.

1 26. The product of claim 24, further comprising
2 instructions for causing the particular network node to:

3 receive from one of the network nodes a packet
4 including a data block and a list of assigned nodes;

5 divide the received list of assigned nodes into a
6 subset of selected assigned nodes, selected according to
7 scoring criteria associated with each assigned node, and a
8 subset of unselected assigned nodes;

9 re-assign each of the unselected assigned nodes to
10 at least one selected assigned node according to the scoring

11 criteria associated with the respective selected assigned
12 nodes;

13 transmit to each selected assigned node a packet
14 including the received data block and a list of the nodes
15 re-assigned to the selected assigned node.

1 27. The product of claim 26, further comprising
2 instructions for causing the particular network node to
3 generate a user discernable output reflecting information in
4 the data block contained in the received packet.

1 28. The product of claim 24, wherein the scoring
2 criteria for at least one recipient node includes the
3 effective bandwidth of that node.

1 29. The product of claim 24, wherein the scoring
2 criteria for at least one recipient node includes the
3 latency between the particular node and the recipient node.

1 30. The product of claim 24, wherein the scoring
2 criteria for at least one recipient node includes the amount
3 of time since a packet from the recipient node was received
4 by the particular node.

1 31. The product of claim 24, wherein the
2 transmitted data block contains audio data.

1 32. The product of claim 24, wherein the
2 transmitted data block contains video data.

1 33. The product of claim 25, wherein the
2 instructions for causing the particular node to assign each
3 unselected node to at least one selected node are

4 instructions for causing the particular node to assign each
5 unselected node to only one selected node.

1 34. A computer program product residing on a
2 computer readable medium comprising instructions for causing
3 a particular network node, connected to a network having a
4 plurality of network nodes, to:

5 receive from one of the network nodes a packet
6 including a data block and a list of assigned nodes;

7 divide the list of assigned nodes into a subset of
8 selected assigned nodes, selected according to scoring
9 criteria associated with each assigned node, and a subset of
10 unselected assigned nodes;

11 re-assign at least one of the unselected assigned
12 nodes to at least one selected assigned node according to
13 the scoring criteria associated with respective selected
14 assigned nodes;

15 transmit to each selected assigned node a packet
16 including the received data block and a list of the nodes
17 re-assigned to the selected assigned node.

1 35. The product of claim 34, further comprising
2 instructions for causing the particular network node to re-
3 assign each of the unselected assigned nodes to at least one
4 selected assigned node.

1 36. The product of claim 34, further comprising
2 instructions for causing the first network node to generate
3 a user discernable output reflecting information in the data
4 block contained in the received packet.

1 37. The product of claim 34, wherein the scoring
2 criteria for at least one node on the list of assigned nodes
3 includes the effective bandwidth of the node.

1 38. The product of claim 34, wherein the scoring
2 criteria for at least one node on the list of assigned nodes
3 includes the latency between that node and the particular
4 network node.

1 39. The product of claim 34, wherein the scoring
2 criteria for at least one node on the list of assigned nodes
3 includes the amount of time since a packet from that node
4 was received by the particular network node.

1 40. The product of claim 34, wherein the
2 transmitted data block contains audio data.

1 41. The product of claim 34, wherein the
2 transmitted data block contains video data.

1 42. The product of claim 35, wherein the
2 instructions for causing the particular network node to re-
3 assign each unselected assigned node to at least one
4 selected assigned node cause the particular network node to
5 re-assign each unselected assigned node to only one selected
6 assigned node.

1 43. A system for transmitting data comprising:
2 a data network;
3 a plurality of network nodes, including at least one
4 sending node;
5 wherein each sending node is programmed to:

6 create a first set of recipient nodes from
7 among the plurality of network nodes;
8 divide the first set of recipient nodes into a
9 subset of selected nodes, selected according to
10 scoring criteria associated with each recipient
11 node, and a subset of unselected nodes;
12 assign at least one of the unselected nodes to
13 at least one selected node according to scoring
14 criteria associated with the respective selected
15 nodes;
16 transmit to each selected node a packet
17 including a data block and a list of the nodes
18 assigned to the selected node.

1 44. The system of claim 43, wherein each sending
2 node is programmed to assign each of the unselected nodes to
3 at least one selected node.

1 45. The system of claim 43, wherein at least one of
2 the plurality of network nodes is programmed to:

3 receive from one of the network nodes a packet
4 including a data block and a list of assigned nodes;

5 divide the list of assigned nodes into a subset of
6 selected assigned nodes, selected according to scoring
7 criteria associated with each assigned node, and a subset of
8 unselected assigned nodes;

9 re-assign each of the unselected assigned nodes to
10 at least one selected assigned node according to the scoring
11 criteria associated with respective selected assigned nodes;

12 transmit to each selected assigned node a packet
13 including the received data block and a list of the nodes
14 re-assigned to the selected assigned node.

1 46. The system of claim 45, wherein the at least
2 one of the plurality of network nodes includes at least two
3 network nodes.

1 47. The system of claim 43, wherein at least two of
2 the network nodes are programmed to generate a user
3 discernable output reflecting information in the data block
4 contained in the received packet.

1 48. The system of claim 43, wherein the scoring
2 criteria for at least one recipient node includes the
3 effective bandwidth of the node.

1 49. The system of claim 43, wherein the scoring
2 criteria for at least one recipient node includes the
3 latency between the sending node and the recipient node.

1 50. The system of claim 43, wherein the scoring
2 criteria for at least one recipient node includes the amount
3 of time since a packet from the recipient node was received
4 by the sending node.

1 51. The system of claim 43, wherein the transmitted
2 data block contains audio data.

1 52. The system of claim 43, wherein the transmitted
2 data block contains video data.

1 53. The system of claim 43, wherein there are at
2 least two sending nodes.

1 54. The system of claim 45, wherein the at least
2 one of the plurality of network nodes includes at least one
3 sending node.

1 55. The system of claim 44, wherein each of the
2 sending nodes is programmed to assign each of the unselected
3 nodes to only one selected node.

1 56. A system for transmitting data comprising:
2 a data network;
3 a plurality of network nodes;
4 wherein at least one particular node of the
5 plurality of network nodes is programmed to:
6 receive from one of the network nodes a packet
7 including a data block and a list of assigned nodes;
8 divide the list of assigned nodes into a subset
9 of selected assigned nodes, selected according to
10 scoring criteria associated with each assigned node,
11 and a subset of unselected assigned nodes;
12 re-assign at least one of the unselected
13 assigned nodes to at least one selected assigned
14 node according to the scoring criteria associated
15 with respective selected assigned nodes;
16 transmit to each selected assigned node a
17 packet including the received data block and a list
18 of the nodes re-assigned to the selected assigned
19 node.

1 57. The system of claim 56, wherein the at least
2 one particular node is programmed to re-assign each of the
3 unselected assigned nodes to at least one selected assigned
4 node.

1 58. The system of claim 56, wherein the at least
2 one particular node includes at least two particular nodes.

1 59. The system of claim 56, wherein at least two of
2 the network nodes are programmed to generate a user
3 discernable output reflecting information in the data block
4 contained in the received packet.

1 60. The system of claim 56, wherein the scoring
2 criteria for at least one node from the list of assigned
3 nodes includes the effective bandwidth of the node.

1 61. The system of claim 56, wherein the scoring
2 criteria for at least one node from the list of assigned
3 nodes includes the latency between the particular node and
4 the assigned node.

1 62. The system of claim 56, wherein the scoring
2 criteria for at least one node from the list of assigned
3 nodes includes the amount of time since a packet from the
4 assigned node was received by the particular node.

1 63. The system of claim 56, wherein the transmitted
2 data block contains audio data.

1 64. The system of claim 56, wherein the transmitted
2 data block contains video data.

1 65. The system of claim 56, wherein there are at
2 least two sending nodes.

1 66. The system of claim 56, wherein the at least
2 one particular node of the plurality of network nodes
3 includes at least one sending node.

1 67. The system of claim 57, wherein the at least
2 one particular node is programmed to re-assign each
3 unselected assigned node to only one selected assigned node.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
22

EFFICIENT TRANSMISSION OF DATA TO MULTIPLE NETWORK NODES

Abstract of the Disclosure

An improved method, system, and computer program product for efficient transmission of data to multiple network nodes is disclosed. A method for transmitting a data block over a network from a first sending node to a first set of recipient nodes, comprises, in the first sending node, a) dividing the first set of recipient nodes into a subset of selected nodes, selected according to scoring criteria associated with each recipient node, and a subset of unselected nodes, b) assigning at least one of the unselected nodes to at least one selected node according to scoring criteria associated with the respective selected nodes, c) transmitting to each selected node a packet including the data block and a list of the nodes assigned to the selected node.

350120.B11





Figure 1



200

Figure 2




Fig. 3

Fig. 4




Figure 5





Figure 6



COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled EFFICIENT TRANSMISSION OF DATA TO MULTIPLE NETWORK NODES, the specification of which

- ☒ is attached hereto.
☐ was filed on _____ as Application Serial No. _____
and was amended on _____.
☐ was described and claimed in PCT International Application No. _____
filed on _____ and as amended under PCT Article 19 on _____.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information I know to be material to patentability in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby appoint the following attorneys and/or agents to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Eric L. Prah, Reg. No. 32,590

Address all telephone calls to Eric L. Prah at telephone number 617/542-5070.

Address all correspondence to Eric L. Prah, Fish & Richardson P.C., 225 Franklin Street, Boston, MA 02110-2804.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patents issued thereon.

Full Name of Inventor: Anthony M. Lovell

Inventor's Signature: _____ Date: _____

Residence Address: Cambridge, MA

Citizen of: U.S.A.

Post Office Address: 149 Richdale Street, Cambridge, MA 02140

COMBINED DECLARATION AND POWER OF ATTORNEY CONTINUED

Full Name of Inventor: Sylvan Clebsch

Inventor's Signature: _____ Date: _____

Residence Address: San Francisco, CA

Citizen of: U.S.A.

Post Office Address: 823 Carolina Street, San Francisco, CA 94107

Full Name of Inventor: Greg Cockroft

Inventor's Signature: _____ Date: _____

Residence Address: Grand Ledge, MI

Citizen of: U.S.A.

Post Office Address: 13780 North River Highway, Grand Ledge, MI 48837

48837 13780 North River Highway, Grand Ledge, MI 48837